



BAVARIA® Portable Dry Chemical Powder Fire Extinguisher External Pressure Cylinder Operated

Type

TORNADO EB



APPLICATIONS

BAVARIA TORNADO EB is designed for protecting high hazard areas, such as industrial and commercial complexes, petroleum company, warehouses, residential buildings, and vehicles

EFFICIENCY

Supreme extinguishing performance rating due to its multipurpose dry chemical powder "BAVARIA Superlative Powder" and easy to use

RELIABILITY

Robust, functional and permanent reliable technology

UNIVERSALITY

Suitable for solid and glowing incendiary substances, liquid substances or substances becoming liquid and gaseous substances

CREDENTIALS

BAVARIA TORNADO EB is approved and certified according to EN3, TÜV, CE, GS and ES 734

SPEED

Open turning valve of external pressure cylinder for immediate readiness, and squeeze pistol lever to attack fire from below

EASY TO HANDLE

Optimized ergonomic grip facilitates easy handling. Equipped with hose and pistol for high maneuverability & control

ECONOMY

Low maintenance due to identical components throughout the series

OPERATION & IMPLEMENTATION

- Simple and easy-to-use release mechanism
- Perfect amount of extinguishing agent due to ergonomically designed head valve & pistol

QUALITY

BAVARIA is certified according to Quality, Environment and OHSAS Management Systems ISO 9001, ISO 14001 and BS-OHSAS 18001



BAVARIA EGYPT (S.A.E.)

Gisir El Suez St. Block 109, Industrial Zone,
Ismailia Desert Road, Cairo-Egypt
P O Box: 2016/11111 Cairo-Egypt

Tel. : +20 (0) 2 2182 0604 / 5 / 6
Fax : +20 (0) 2 2182 0609
Website : www.bavaria-firefighting.com
Email : international.sales@bavaria.com.eg



BAVARIA Brandschutz Industrie GmbH & Co. KG

Regensburger StraBe16,
D-93449 Waldmunchen
Germany

Tel. : +49 (0) 9972 9401-0
Fax : +49 (0) 9972 9401-17
Website : www.bavaria-firefighting.de
Email : info@bavaria-firefighting.de

Germany - Egypt - Lebanon

2 plants in Europe and Middle East, 250 dealers worldwide

Together....
against Fire



BAVARIA® Portable Dry Chemical Powder Fire Extinguisher - External Pressure Cylinder Operated

Type: **TORNADO EB - High Hazard ★★★★★**

Features:

- Supreme extinguishing rating
- Allows intermittent and repeated operation
- Designed with an aluminum alloy head
- Equipped with a rechargeable external pressure cylinder
- Operated with a high pressure reinforced rubber hose and pistol for high maneuverability and control
- High quality surface treatment and red polyester coating
- Electricity and corrosion proof-protective base
- Supplied with a special hanging wall bracket
- Affords the highest extinguishing rating due to its multipurpose dry chemical powder "BAVARIA Superlative Powder"
- Suitable only for electrical equipment up to 1000 V, at minimum distance 1 m



European Standard DIN/EN3 Certified
 The extinguishing media (dry chemical powder) is certified according to the European Norm EN 615
 Egyptian Standard ES 734 Certified
 TÜV (SÜD Deutschland) Approved Pressure Vessel
 Awarded the European (CE) mark and the German Geprüfte Sicherheit (GS) Mark
 The Company is Certified according to Quality, Environment and OHSAS Management Systems ISO 9001, ISO 14001 & BS-OHSAS 18001
 Bavaria Laboratory Accredited According to the ISO/IEC 17025

Technical Specifications:

Capacity	6 kg	9 kg	12 kg
Extinguishing Rating	43A 233B C (+R)*	55A 233B C (+R)*	55A 233B C (+R)*
Operating Temperature Range*	-30 °C to +60 °C	-30 °C to +60 °C	-30 °C to +60 °C
Testing Pressure	35 bar	35 bar	35 bar
Bursting Pressure	Over 70 bar	Over 70 bar	Over 70 bar
Valve Material	Aluminum alloy head		
Discharge Pistol Material	Special engineered polymer		
Shell Material	DC 04 Steel according to DIN EN 10130		
Extinguishing Agent	MAP-based " BAVARIA Superlative Powder"		
Expellant Gas Weight	160 gm	270 gm	290 gm
Propellant Gas	CO ₂	CO ₂	CO ₂
Paint Finish	Surface treatment and 100% polyester coating		
Approx. Gross Weight	11.8 kg	17.2 kg	20.5 kg
Approx. Unit Dimension (l x w x h) cm	28.0 x 17.5 x 54.0	30.0 x 21.0 x 56.0	30.0 x 20.5 x 68.0

* (+R) Plus Powder Reserve

* This product is certified to fully operate at temperatures up to +70 °C according to ES 734 Standard

Warranty:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity

* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.