



BAVARIA® Wheeled Foam Fire Extinguishers External Pressure Cylinder Operated

TORNADO-F



APPLICATIONS

BAVARIA TORNADO-F fire extinguisher with its stainless steel bright elegant shape is optimum for use in petrol stations, boiler rooms, designed for protection against fires of flammable solvents

EFFICIENCY

Supreme extinguishing performance rating due to its AFFF foam, and easy to use
The extinguisher filled by AFFF 3% pre-mixed foam concentrate, certified and approved according the European standard EN 1568-3 with fire rating IA/IA with both both potable water and sea water, and approved according to the UL162

RELIABILITY

Robust, functional and permanent reliable technology

UNIVERSALITY

Suitable for petrol stations, boiler rooms, designed for protection against fires of flammable solvents

CREDENTIALS

Unified operating concept for all types of external pressure cylinder operated extinguishers. TÜV Approved

SPEED

Open turning valve of external pressure cylinder for immediate readiness, and squeeze pistol lever to attack fire from below

EASY TO USE

Supported on a carriage with two rear rollers and a front directional roller for easier maneuvering. Equipped with a reinforced rubber hose for control

QUALITY

BAVARIA is certified according to Quality, Environment and Management Systems, ISO 9001, ISO 14001 and ISO 45001.



BAVARIA EGYPT (S.A.E.)
Gisr El Suez St. Block 109, Industrial Zone,
Ismailia Desert Road, Cairo-Egypt
P O Box: 2016/11111 Cairo-Egypt

Tel. : +20 (0) 2 2182 0604 / 5 / 6
Fax : +20 (0) 2 2182 0609
Website : www.bavaria-firefighting.com
Email : international.sales@bavaria.com.eg



BAVARIA Brandschutz Industrie GmbH & Co. KG
Regensburger StraBe16,
D-93449 Waldmunchen
Germany

Tel. : +49 (0) 9972 9401-0
Fax : +49 (0) 9972 9401-17
Website : www.bavaria-firefighting.de
Email : info@bavaria-firefighting.de



BAVARIA® Wheeled Foam Fire Extinguishers - External Pressure Cylinder Operated

FEATURES:

- Supreme extinguishing efficiency
- One man-operated for easy and efficient use
- Allows repeated operation and intermittence at will
- Chrome-plated valve head with mechanical over-pressure safety valve
- Equipped with pressure release valve and pressure gauge for pressure control
- Propelled with external nitrogen cylinder
- Equipped with reinforced rubber hose
- Equipped with a heat and an electricity-isolated operating pistol
- Supported on a carriage with two rear rollers and a front directional roller for easier manoeuvring, with chemical-resistant tyres



TYPE: **TORNADO -F**
HIGH HAZARD ★★★★★

Manufactured According to European Standard DIN/EN 1866

BAVARIA is certified according to Quality, Environment and Management Systems, ISO 9001, ISO 14001 and ISO 45001.
Bavaria Laboratory Accredited According to the ISO/IEC 17025

TECHNICAL SPECIFICATIONS:

Capacity	45 l	90 l
Fire Classes	AB	AB
Operating Temperature Range	+5 °C to +60 °C (with additive)	
Testing Pressure	35 bar	35 bar
Bursting Pressure	Over 70 bar	Over 70 bar
Closure Material	Chrome plated metal alloy	
Shell Material	Stainless Steel	Stainless Steel
Extinguishing Agent	BAVARIA Typhoon AFFF 3% pre-mixed foam (Rating IA/IA)	
Reinforced Rubber Hose	5 m length	10 m length
External Pressure Cylinder	3 l	7 l
Propellant Gas	N ₂	N ₂
External Cylinder Test Pressure	250 bar	250 bar
Approx Gross Weight	123.0 kg	237.0 kg
Manufactured according to European Standard DIN/EN 1866		

WARRANTY:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity

* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.