



BAVARIA Fire Fighting Solutions

When It Comes To Your Safety Only The BEST Is Good Enough



# BAVARIA® Wheeled Dry Chemical Powder Fire Extinguishers Stored Pressure Operated

## CONCORD-25



### APPLICATIONS

BAVARIA CONCORD-25 is a rapid intervention, one man operational unit for effective fire fighting

### EFFICIENCY

Supreme extinguishing performance rating due to its multipurpose dry chemical powder "BAVARIA Superlative Powder" and easy to use

### RELIABILITY

Robust, functional and permanent reliable technology

### UNIVERSALITY

Suitable for solid and glowing incendiary substances, liquid substances or substances becoming liquid and gaseous substances

### CREDENTIALS

Unified operating concept for all types of external pressure cylinder operated extinguishers. manufactured according to EN1866 and approved TÜV, CE, ES 1494

### SPEED

Open head valve of fire extinguisher for immediate readiness, and squeeze pistol lever to attack fire from below

### EASY TO USE

Supported on two rear rollers and a front directional roller for easier maneuvering. Equipped with a reinforced rubber hose and pistol for control

### ECONOMY

Low maintenance due to identical components throughout the series

### QUALITY

BAVARIA is certified according to Quality, Environment and Management Systems, ISO 9001, ISO 14001 and ISO 45001.



**BAVARIA EGYPT (S.A.E.)**  
Gisr El Suez St. Block 109, Industrial Zone,  
Ismailia Desert Road, Cairo-Egypt  
P O Box: 2016/11111 Cairo-Egypt

Tel. : +20 (0) 2 2182 0604 / 5 / 6  
Fax : +20 (0) 2 2182 0609  
Website : [www.bavaria-firefighting.com](http://www.bavaria-firefighting.com)  
Email : [international.sales@bavaria.com.eg](mailto:international.sales@bavaria.com.eg)



**BAVARIA Brandschutz Industrie GmbH & Co. KG**  
Regensburger StraBe16,  
D-93449 Waldmunchen  
Germany

Tel. : +49 (0) 9972 9401-0  
Fax : +49 (0) 9972 9401-17  
Website : [www.bavaria-firefighting.de](http://www.bavaria-firefighting.de)  
Email : [info@bavaria-firefighting.de](mailto:info@bavaria-firefighting.de)



# BAVARIA® Wheeled Dry Chemical Powder Fire Extinguishers - Stored Pressure Operated

## FEATURES:

- High extinguishing efficiency
- A one man-operational unit
- Allows repeated operation and intermittence at will
- Equipped with a pressure filling/release valve and a pressure gauge
- Equipped with a 5 m reinforced rubber hose for easy manoeuvring
- Equipped with a heat & an electricity-isolated operating pistol
- Supported on a carriage with two rear rollers and a front directional roller for easier manoeuvring
- Affords the highest extinguishing rating due to its multipurpose dry chemical powder "BAVARIA Superlative Powder" (ABC)
- Suitable for electrical equipment up to 1000 V, at minimum distance 1 m



TYPE: **CONCORD - 25**  
MEDIUM HAZARD ★★★★★

Manufactured According to European Standard DIN/EN 1866

The extinguishing media (dry chemical powder) is certified according to the European Norm EN 615

Certified According to Egyptian Standard ES 1494

TÜV (SÜD Deutschland) Approved Pressure Vessel

Awarded the European (CE) mark

BAVARIA is certified according to Quality, Environment and Management Systems, ISO 9001, ISO 14001 and ISO 45001.

Bavaria Laboratory Accredited According to the ISO/IEC 17025

## TECHNICAL SPECIFICATIONS:

Capacity	25 kg
Extinguishing Rating	A IB C
Operating Temperature Range*	-20 °C to +60 °C
Testing Pressure	35 bar
Bursting Pressure	Over 70 bar
Valve Material	Chrome plated brass alloy with a manometer & filling/release valve
Discharge Pistol Material	Special engineered polymer
Shell Material	Steel according to EN 10028-3
Extinguishing Agent	MAP-based "BAVARIA Superlative Powder"
Hose	Reinforced rubber hose 5 m length
Paint Finish	Surface treatment and 100% polyester coating
Approx Gross Weight	75.0 kg
* Manufactured according to European Standard DIN EN 1866	
* This product is certified to fully operate at temperatures up to +70 °C according to ES 1494 Standard	

## WARRANTY:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity

\* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.