

Fire Fighting Solutions



BAVARIA® Portable Dry Chemical Powder Fire Extinguishers

Internal Cartridge Operated

ype

Vora X P



APPLICATIONS

BAVARIA Vora X-P is a high performing, universal ABC powder extinguisher. The extinguisher can be used in various areas, for example: in the industry and trade, municipal insti-tutions, households and in all areas, where comprehensive, preventive fire protection needs to be insured













BAVARIA EGYPT (S.A.E.)

Gisr El Suez St. Block 109, Industrial Zone Ismailia Desert Road, Cairo - Egypt P O Box: 2016/11111 Cairo - Egypt



BAVARIA Brandschutz Industrie GmbH & Co. KG

Regensburger StraBe16, D-93449 Waldmunchen Germany Tel. : + 20 (2) 2182 0604 / 5 / 6
Fax : + 20 (2) 2182 0609
Website : www.bavaria-firefighting.com
Email : international.sales@bavaria.com.eg

Tel. : + 49 (0) 997 29 401-0 Fax : + 49 (0) 997 29 401-17 Website : www.bavaria-firefighting.de Email : info@bavaria-firefighting.de



Fire Fighting Solutions



BAVARIA® Portable Dry Chemical Powder Fire Extinguishers - internal cartridge Operated

Type: Vora X P - Low Hazard ★★★★

Features:

- High extinguishing rating
- Allows intermittent and repeated extinguishing.
- Valve is completely nickel-plated with a contrasting red activation button.
- Operated with a high pressure reinforced rubber EPDM-hose and pistol for a high manoeuvrability and control
- A flapper valve for the safe and easy activation.
- Throughout the special polyester coating of the cylinder, the extinguisher has a high corrosion protection.
- The special BAVARIA ABC rated extinguishing agent guarantees a high extinguishing rating.
- Suitable for electrical systems up to 1000 V, with a min. distance of 1 m.
- Supplied with a high quality wall bracket.



Compliant with the European Standard DIN/EN3
TÜV-certified pressure cylinder
CE marked

Management System certified according oh ISO 9001

Technical Specifications:

Type / Amount of the agent	Vora X-P / 6 kg
Test object	43A 233B C
Range of operating temperature from	-30°C to +60°C
Testing pressure	30 bar
Bursting pressure	min. 55 bar
Valve	Nickle plated
Material of the cylinder	DC 04
Propellant	CO2
Amount of propellant	140 gr.
Extinguishing agent	ABC powder
Coating	Polyester
Approx	gross weight 11,4 kg
Approx.	dimension (LxWxH) 22,5x15,5x55 cm
Packaging material	Cardboard
Functional time	approx. 15 sec.
Approx. range of throw	approx. 6 m

Warranty:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity

^{*} The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.