



BAVARIA® Portable Water Fire Extinguisher Internal Cartridge Operated

MAGNUM AQUA-JET



APPLICATIONS

MAGNUM AQUA-JET is a water Water Fire Extinguishers discharge a stream of water onto the fire, lowering the temperature of the burning material to below ignition point

EFFICIENCY

Effective extinguishing performance rating due to its agent & easy to use

RELIABILITY

Robust, functional and permanent reliable technology

UNIVERSALITY

Suitable for the following types of fires: Class A – Paper, textiles, wood, most plastics & rubber

CREDENTIALS

MAGNUM AQUA-JET is approved and certified according to EN3, TÜV, CE and GS

SPEED

Strike button valve in combination of high-quality metering, pistol ensures immediate readiness

EASY TO HANDLE

Optimized ergonomic grip facilitates easy handling, hose with pistol for high maneuverability and control

ECONOMY

Low maintenance due to identical components throughout the series

OPERATION & IMPLEMENTATION

- Simple and easy-to-use release mechanism
- Perfect amount of extinguishing agent due to ergonomically designed head valve & pistol

QUALITY

BAVARIA is certified according to Quality, Environment and Management Systems ISO 9001, ISO 14001 and ISO 45001



BAVARIA EGYPT (S.A.E.)
Gisir El Suez St. Block 109, Industrial Zone,
Ismailia Desert Road, Cairo-Egypt
P O Box: 2016/11111 Cairo-Egypt

Tel. : +20 (0) 2 2182 0604 / 5 / 6
Fax : +20 (0) 2 2182 0609
Website : www.bavaria-firefighting.com
Email : international.sales@bavaria.com.eg



BAVARIA Brandschutz Industrie GmbH & Co. KG
Regensburger StraBe16,
D-93449 Waldmünchen
Germany

Tel. : +49 (0) 9972 9401-0
Fax : +49 (0) 9972 9401-17
Website : www.bavaria-firefighting.de
Email : info@bavaria-firefighting.de



BAVARIA® Portable Water Fire Extinguisher - internal cartridge Operated

FEATURES:

- High extinguishing efficiency
- Filled with 6 l or 9 l water and additives
- Allows intermittent and repeated operation
- Designed with a special engineered polymer head equipped with an over pressure mechanical safety valve
- Equipped with a rechargeable internal gas pressure cartridge
- Internally coated with a special protective polymer lining, affording full protection against corrosion
- Operated with a high pressure rubber hose and pistol for high maneuverability and control
- Heat & electricity-isolated operation pistol & corrosion-proof base
- High quality surface treatment and red polyester coating
- Supplied with special hanging wall bracket



TYPE: MAGNUM AQUA-JET
MEDIUM HAZARD ★★★★★

European Standard DIN/EN3 Certified

TÜV (SÜD Deutschland) Approved Pressure Vessel

Awarded the European (CE) mark and the German Geprüfte Sicherheit (GS) Mark

BAVARIA is certified according to Quality, Environment and Management Systems ISO 9001, ISO 14001 and ISO 45001

Bavaria Laboratory Accredited According to the ISO/IEC 17025

TECHNICAL SPECIFICATIONS:

Capacity	6 l	9 l
Extinguishing Rating	34 A	34 A
Operating Temperature Range	0 °C to +60 °C (with additives)	
Testing Pressure	27 bar	
Bursting Pressure	Over 70 bar	
Valve Material	Special engineered polymer	
Discharge Pistol Material	Special engineered polymer	
Shell Material	DC 04 Steel according to DIN EN 10130	
Extinguishing Agent	Water + Additives	
Expellant Gas Weight	50 gm	70 gm
Propellant Gas	CO ₂	
Internal Lining	Elastic polymer	
Paint Finish	Surface treatment and 100% polyester coating	
Approx. Gross Weight	10.9 kg	16.0 kg
Approx. Unit Dimension (lxwxh) cm	28.0 x 16.5 x 57.5 cm	30.0 x 20.0 x 57.5 cm

WARRANTY:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity

* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.