

**BAVARIA**

Fire Fighting Solutions

When It Comes To Your Safety Only The BEST Is Good Enough

**BAVARIA**

## **BAVARIA®** Portable Carbon Dioxide Fire Extinguisher

Type

**SIGMA 2**

### Applications:

BAVARIA SIGMA Carbon Dioxide fire extinguisher is effective in fighting flammable liquids and electric fires

**BAVARIA**

**BAVARIA** EGYPT (S.A.E.)  
Gisir El Suez St. Block 109, Industrial Zone,  
Ismailia Desert Road, Cairo-Egypt  
P O Box: 2016/11111 Cairo-Egypt

Tel. : + 20 (2) 2698 9443 / 5 / 6  
Fax : + 20 (2) 2698 8447  
Website : [www.bavaria-firefighting.com](http://www.bavaria-firefighting.com)  
Email : [international.sales@bavaria.com.eg](mailto:international.sales@bavaria.com.eg)

**BAVARIA**

**BAVARIA** Brandschutz Industrie GmbH & Co. KG  
Regensburger Str. 16,  
93449 Waldmünchen  
Germany

Tel. : + 49 (0) 9972 9401-0  
Fax : + 49 (0) 9972 9401-17  
Website : [www.bavaria-firefighting.com](http://www.bavaria-firefighting.com)  
Email : [info@bavaria-brandschutz.de](mailto:info@bavaria-brandschutz.de)

Germany - Egypt - Lebanon - Sudan - U.A.E.

1/2

## **BAVARIA®** Portable Carbon Dioxide Fire Extinguisher

Type: **SIGMA 2**

### Features:

- Suitable for fighting flammable liquids and electric fires
- Carbon dioxide is a clean agent that leaves no traces, thus ideal for fighting fires involving electronic & hi-tech equipment
- Allows intermittent and repeated operation
- Equipped with a brass valve head complete with an overpressure safety valve
- Equipped with a squeeze-type valve, conical snow horn, and carrying handle
- High quality surface treatment and red polyester coating
- Delivered with its special wall bracket



European Standard DIN/EN3 Certified  
TÜV (SÜD Deutschland) Approved Pressure Vessel  
Awarded **CE** Mark

The Company Certified according to Quality Management System ISO 9001  
Bavaria Laboratory Accredited According to the ISO/IEC 17025

### Technical Specifications:

Capacity	2 kg
Fire Classes	34 B
Working Temperature Range	-30 °C to 60 °C
Cylinder	Seamless steel cylinder
Testing Pressure	310 bar
Bursting Pressure	Min 500 bar
Valve Material	Brass valve complete with overpressure safety valve
Discharge fitting	Plastic conical snow horn
Extinguishing Agent	CO <sub>2</sub>
Paint Finish	Surface treatment and 100% polyester coating
Approx. Gross Weight	7.1 Kg
Approx. Unit Dimension (lxwxh) cm	25.0x11.0x55.0

### Warranty:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity

\* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.