

Fire Fighting Solutions



## **BAVARIA®** Mobile Dry Chemical Powder Fire Extinguishers

**External Pressure Cylinder Operated** 

# **TORNADO - 100**



## APPLICATIONS

BAVARIA TORNADO-100 is a rapid intervention, one man operational unit for effective fire fighting

## EFFICIENCY

Supreme extinguishing performance rating due to its multipurpose dry chemical powder "BAVARIA Superlative Powder" and easy to use

## RELIABILITY

Robust, functional and permanent reliable technology

## UNIVERSALITY

Suitable for solid and glowing incendiary substances, liquid substances or substances becoming liquid and gaseous substances

## INTEGRITY

Unified operating concept for all types of external pressure cylinder operated extinguishers. Approved EN1866, TÜV, CE, GS, ES 1494, and BAVARIA is certified according to Quality, Environment and OHSAS Management Systems ISO 9001, ISO 14001 & BS-OHSAS 18001

### SPEED

Open turning valve of external pressure cylinder for immediate readiness, and squeeze pistol lever to attack fire from below

## EASY TO USE

Supported on two rear rollers and a front directional roller for easier maneuvering. Equipped with a reinforced rubber hose for control.

#### ECONOMY

Low maintenance due to identical components throughout the series



Tel.

Fax



















## BAVARIA EGYPT (S.A.E.)

Gisr El Suez St. Block 109, Industrial Zone, Ismailia Desert Road, Cairo-Egypt P O Box: 2016/11111 Cairo-Egypt



#### BAVARIA Brandschutz Industrie GmbH & Co. KG

Germany - Egypt - Lebanon - Sudan - U.A.E.

2 plants in Europe and Middle East, 250 dealers worldwide

Regensburger StraBe16, D-93449 Waldmunchen Germany

> Together.... against Fire

: + 20 (2) 2182 0604 / 5 / 6 : + 20 (2) 2182 0609 Fax

Website: www.bavaria-firefighting.com : international.sales@bavaria.com.eg Email

: +49 (0) 997 29 401-0

: + 49 (0) 997 29 401-17

Website: www.bavaria-firefighting.de : info@bavaria-firefighting.de



Fire Fighting Solutions



## **BAVARIA** Mobile Dry Chemical Powder Fire Extinguishers - External Pressure Cylinder Operated

Type: TORNADO - 100 High Hazard ★★★★★

#### **Features:**

- Supreme extinguishing efficiency
- A one man-operational unit
- Allows repeated operation and intermittence at will
- Equipped with a pressure release valve and a pressure gauge
- Equipped with chrome plated brass alloy with closure a mechanical over-pressure safety valve
- Equipped with a 10 m reinforced rubber hose for easy manoeuvring
- Propelled with a 10 I external pressure cylinder
- Equipped with a heat & an electricity-isolated operating pistol
- Supported on 2-rear rollers and a front directional roller for easier manoeuvring with chemical-resistant tyres
- Affords the highest extinguishing rating due to its multipurpose dry chemical powder "BAVARIA Superlative Powder" (ABC)
- Suitable for electrical equipment up to 1000 V, at minimum distance 1 m



Manufactured According to European Standard DIN/EN 1866 Certified According to Egyptian Standard ES 1494 TÜV Approved Pressure Vessel Awarded **C€** Mark

The Company is Certified according to Quality, Environment and BS-OHSAS Management Systems ISO 9001, ISO 14001 Bavaria Laboratory Accredited According to the ISO/IEC 17025

## **Technical Specifications:**

| Capacity                     | 100 kg  |
|------------------------------|---|
| Extinguishing Rating         | A IIIB C  |
| Operating Temperature Range* | -20 °C to +60 °C  |
| Testing Pressure             | 35 bar  |
| Bursting Pressure            | Over 70 bar   |
| Closure Material             | Chrome plated brass alloy                                       |
| Shell Material               | Steel according to EN 10028-3                                   |
| Extinguishing Agent          | MAP-based "BAVARIA Superlative Powder"                          |
| Hose                         | Reinforced rubber hose 10 m Length                              |
| External Pressure Cylinder   | 10  |
| Propellant Gas               | $N_2$   |
| Paint Finish                 | Surface treatment and 100% polyester coating                    |
| Approx Gross Weight          | 230.0 kg  |
| Option at Extra Cost         | Trapaulin protective cover from weathering factors upon request |
|                              |   |

## Warranty:

| Period of Warranty          | 2 Years  |
|-----------------------------|--|
| Coverage of the Warranty    | Against material failure and production defects  |
| Method of Warranty Coverage | Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty |
| Warranty Exclusions         | Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity                                       |
|                             | ·  |

The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order,

Manufactured according to European Standard DIN EN 1866 \* This product is certified to fully operate at temperatures up to +70 °C according to ES 1494 Standard